



MURSATT CHEMICALS LIMITED
11 REGALCREST COURT
WOODBIDGE; ONTARIO, CANADA; L4L 8P3
(905)-850-8444

PRODUCT: 40-WINKS

CODE: MUR0040

Section 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER/SUPPLIER..... MURSATT CHEMICALS LIMITED
11 REGALCREST COURT
WOODBIDGE, ONTARIO
CANADA
L4L 8P3
PREPARED BY..... REGULATORY AFFAIRS
PREPARATION DATE..... Jun01/08
PRODUCT NAME..... 40-WINKS
PRODUCT CODE..... MUR0040
CHEMICAL FORMULA..... MIXTURE.
MOLECULAR WEIGHT..... MIXTURE.
CHEMICAL FAMILY..... MIXTURE.
MATERIAL USE..... SWIMMING POOL EQUIPMENT CLEANER.
EMERGENCY PHONE NO..... CANUTEC (613)-996-6666.

Section 02: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients	%	Exposure Limit	C.A.S.#	LD/50, Route, Species	LC/50 Route, Species
ALKYL DIMETHYL BENZYL AMMONIUM CHLORIDE (C12-18)	10-30	N.AV.	68391-01-5	N.AV.	N.AV.
ALKYL (68% C12, 32% C14) DIMETHYL ETHYLBENZYL AMMONIUM CHLORIDE	10-30	N.AV.	85409-23-0	N.AV.	N.AV.
ETHANOL	5-10	SEE SECTION 11	64-17-5	SEE SECTION 11	SEE SECTION 11

Section 03: HAZARDS IDENTIFICATION

ROUTE OF ENTRY:
SKIN CONTACT..... THIS PRODUCT MAY BE CORROSIVE TO THE SKIN.
SKIN ABSORPTION..... THIS PRODUCT MAY BE HARMFUL IF IT IS ABSORBED THROUGH THE SKIN.
EYE CONTACT..... THIS PRODUCT MAY BE CORROSIVE TO EYES.
INHALATION..... EXPOSURE VIA INHALATION NOT LIKELY.HIGH VAPOR CONCENTRATIONS MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS.EFFECTS MAY INCLUDE HEADACHES, DIZZINESS, DROWSINESS, ANESTHETIC AND MAY HAVE OTHER CENTRAL NERVOUS SYSTEM EFFECTS.
INGESTION..... THIS PRODUCT MAY BE FATAL IF IT IS SWALLOWED.
EFFECTS OF ACUTE EXPOSURE..... SEE ABOVE.
EFFECTS OF CHRONIC EXPOSURE..... SEE ABOVE.
INHALATION, CHRONIC..... SEE ABOVE.

Section 04: FIRST AID MEASURES

EYE CONTACT..... IMMEDIATELY FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES, WHILE HOLDING EYELIDS OPEN. SEEK MEDICAL ATTENTION AT ONCE. .
SKIN CONTACT..... IMMEDIATELY TAKE OFF ALL CONTAMINATED CLOTHING.WASH CONTAMINATED CLOTHING BEFORE REUSE.FOR SKIN CONTACT FLUSH WITH LARGE AMOUNTS OF WATER.GET MEDICAL ATTENTION OR ADVICE.
INGESTION..... IF THE MATERIAL IS SWALLOWED, GET IMMEDIATE MEDICAL ATTENTION OR ADVICE. NEVER GIVE ANYTHING BY MOUTH TO A VICTIM WHO IS UNCONSCIOUS OR IS HAVING CONVULSIONS. DO NOT INDUCE VOMITING.
INHALATION..... IF SYMPTOMS ARE EXPERIENCED, REMOVE SOURCE OF CONTAMINATION OR MOVE VICTIM TO FRESH AIR.IF SYMPTOMS PERSIST, GET MEDICAL ATTENTION.IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION, PREFERABLY MOUTH-TO-MOUTH. IF BREATHING IS DIFFICULT, GIVE OXYGEN.SEEK MEDICAL ATTENTION.
NOTES TO PHYSICIAN..... IF THE PRODUCT IS INGESTED, PROBABLE MUCOSAL DAMAGE MAY CONTRAINDICATE THE USE OF GASTRIC LAVAGE. TREAT THE AFFECTED PERSON APPROPRIATELY. .

PRODUCT: 40-WINKS

CODE: MUR0040

Section 05: FIRE FIGHTING MEASURES

T.D.G. FLAM. CLASS..... 3.
 FLAMMABILITY..... FLAMMABLE. OSHA FLAMMABILITY CLASSIFICATION: COMBUSTIBLE II.
 IF YES, UNDER WHICH CONDITIONS?
 EXTINGUISHING MEDIA..... DRY CHEMICAL, FOAM, CARBON DIOXIDE, WATER FOG. USE WATER TO COOL FIRE-EXPOSED CONTAINERS AND TO PROTECT PERSONNEL.
 SPECIAL PROCEDURES..... FIREFIGHTERS SHOULD WEAR FULL FIRE-FIGHTING TURN-OUT GEAR (FULL BUNKER GEAR) INCLUDING NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN THE PRESSURE DEMAND OR OTHER POSITIVE PRESSURE MODE.
 FLASH POINT (C), METHOD..... >(39.4 °C), 103 F PMCC.
 AUTO IGNITION TEMPERATURE..... N.AV.
 UPPER FLAMMABLE LIMIT (% BY VOL.)... N.AV.
 LOWER FLAMMABLE LIMIT (% BY VOL.)... N.AV.
 EXPLOSION DATA..... N.AV.
 EXPLOSIVE POWER..... N.AV.
 RATE OF BURNING..... N.AV.
 SENSITIVITY TO STATIC DISCHARGE..... N.AV.
 SENSITIVITY TO IMPACT..... N.AV.
 HAZARDOUS COMBUSTION PRODUCTS.. CARBON DIOXIDE AND CARBON MONOXIDE. AMMONIA. NITROGEN OXIDES.

Section 06: ACCIDENTAL RELEASE MEASURES

LEAK/SPILL..... ISOLATE SPILL OR LEAK AREA IMMEDIATELY. KEEP UNAUTHORIZED PERSONNEL AWAY. VENTILATE ENCLOSED AREAS. WEAR APPROPRIATE PROTECTIVE EQUIPMENT. ABSORB WITH AN INERT ABSORBENT. COLLECT IN SUITABLE AND PROPERLY LABELED CONTAINERS. WASH AFFECTED AREA WITH WATER. KEEP FROM ENTERING WATERWAYS OR SEWERS. COLLECT AND CONTAIN FOR DISPOSAL.

Section 07: HANDLING AND STORAGE

HANDLING PROCEDURES AND AVOID CONTACT WITH SKIN AND EYES. WASH HANDS BEFORE EATING, DRINKING, EQUIPMENT SMOKING, OR USING TOILET FACILITIES. WASH THOROUGHLY AFTER WORK USING SOAP AND WATER. AS WITH ALL CHEMICALS, GOOD INDUSTRIAL HYGIENE PRACTICES SHOULD BE FOLLOWED WHEN HANDLING THIS MATERIAL.
 STORAGE NEEDS..... DO NOT HANDLE OR STORE NEAR AN OPEN FLAME, HEAT OR OTHER SOURCES OF IGNITION. STORE IN A COOL, DRY, WELL-VENTILATED AREA.

Section 08: EXPOSURE CONTROLS/PERSONAL PROTECTION

GLOVES/ TYPE..... IMPERVIOUS GLOVES.
 RESPIRATORY/TYPE..... IF IRRITATION IS EXPERIENCED, A NIOSH-APPROVED RESPIRATOR SHOULD BE WORN. VENTILATION AND OTHER FORMS OF ENGINEERING CONTROLS ARE OFTEN THE PREFERRED MEANS FOR CONTROLLING CHEMICAL EXPOSURES. RESPIRATORY PROTECTION MAY BE NEEDED FOR NON-ROUTINE OR EMERGENCY SITUATIONS.
 EYE/TYPE..... WEAR CHEMICAL GOGGLES; FACE SHIELD (IF SPLASHING IS POSSIBLE).
 FOOTWEAR/TYPE..... SEE BELOW.
 CLOTHING/TYPE..... SKIN CONTACT SHOULD BE PREVENTED THROUGH USE OF SUITABLE PROTECTIVE CLOTHING, GLOVES AND FOOTWEAR, SELECTED WITH REGARD FOR USE CONDITIONS AND EXPOSURE POTENTIAL. CONSIDERATION MUST BE GIVEN BOTH TO DURABILITY AS WELL AS PERMEATION RESISTANCE.
 OTHER/TYPE..... EYEWASH STATION AND SAFETY SHOWER IN WORK AREA.
 ENGINEERING CONTROLS..... GENERAL VENTILATION. LOCAL EXHAUST FOR MISTS AND VAPOURS.

Section 09: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE..... LIQUID.
 COLOR..... WATER-WHITE.
 ODOUR..... SLIGHT SWEET.
 ODOUR THRESHOLD..... N.AV.
 VAPOUR PRESSURE (MMHG)..... N.AV.
 VAPOUR DENSITY (AIR=1)
 BY VOLUME..... N.AV.
 BY WEIGHT..... N.AV.
 EVAPORATION RATE..... N.AV.
 BOILING POINT..... N.AV.
 PH..... 7.5.
 SPECIFIC GRAVITY (WATER=1)..... 0.97.
 SOLUBILITY IN WATER (% W/W)..... SOLUBLE.
 COEFFICIENT OF WATER/OIL DIST..... N.AV.

PRODUCT: 40-WINKS

CODE: MUR0040

Section 10: STABILITY AND REACTIVITY

CHEMICAL STABILITY:
 YES..... STABLE.
 NO, WHICH CONDITIONS?
 CONDITIONS TO AVOID..... KEEP AWAY FROM HEAT, SPARKS, OR OPEN FLAME.
 COMPATABILITY WITH OTHER
 SUBSTANCES:
 YES
 NO, WHICH ONES?..... OXIDIZING AGENTS.
 REACTIVITY CONDITIONS:..... CONTACT WITH INCOMPATIBLES.
 HAZARDOUS PRODUCTS OF CARBON MONOXIDE, CARBON DIOXIDE. AMMONIA. NITROGEN OXIDES.
 DECOMPOSITION
 HAZARDOUS POLYMERIZATION..... WILL NOT OCCUR.

Section 11: TOXICOLOGICAL INFORMATION

EXPOSURE LIMIT OF MATERIAL..... FOR ETHANOL 64-17-5: ACGIH - THRESHOLD LIMITS VALUES - TIME WEIGHTED AVERAGES (TLV-TWA) 1000 PPM TWA.
 LC 50 OF MATERIAL, SPECIES & ROUTE.. FOR ETHANOL 64-17-5: TOXICOLOGY DATA - SELECTED LC50S INHALATION LC50 RAT: 124.7 MG/L/4H.
 LD 50 OF MATERIAL, SPECIES & ROUTE.. ORAL LD50 (RAT) = >50 - 500 MG/KG. FOR ETHANOL 64-17-5: TOXICOLOGY DATA - SELECTED LD50S: ORAL LD50 RAT: 1501 MG/KG.
 CARCINOGENICITY OF MATERIAL..... COMPONENTS ARE NOT LISTED CARCINOGENS.
 REPRODUCTIVE EFFECTS..... N.AV.
 DEVELOPMENTAL TOXICITY..... N.AV.
 IRRITANCY OF MATERIAL..... SEE SECTION 03.
 SENSITIZING CAPABILITY OF MATERIAL. N.AV.
 SYNERGISTIC MATERIALS..... N.AV.
 MUTAGENICITY..... N.AV.
 TERATOGENICITY..... N.AV.

Section 12: ECOLOGICAL CONSIDERATIONS

ECOLOGICAL INFORMATION..... N.AV.

Section 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL..... DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS.

Section 14: TRANSPORT INFORMATION

TDG CLASSIFICATION..... 8 (3).
 PROPER SHIPPING NAME..... CORROSIVE LIQUID, FLAMMABLE, N.O.S., (ALKYL DIMETHYL BENZYL AMMONIUM CHLORIDE, ETHANOL).
 UN NUMBER..... 2920.
 PACKING GROUP..... II.
 SPECIAL SHIPPING INSTRUCTIONS..... NO SPECIAL SHIPPING REQUIREMENTS.

Section 15: REGULATORY INFORMATION

CPR COMPLIANCE..... THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CPR AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.
 WHMIS CLASSIFICATION..... B3, D2A, E.

Section 16: OTHER INFORMATION

N.AP.=NOT APPLICABLE
 N.AV.=NOT AVAILABLE
 OTHER INFORMATION..... THE DATA IN THIS MSDS RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED HEREIN AND DOES NOT RELATE TO USE IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY PROCESS. THIS DATA IS OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS PRODUCT SPECIFICATIONS. NO WARRANTY, EITHER EXPRESSED OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE AND DETERMINE WHETHER THEY ARE APPROPRIATE.